Separator with Tank Reduce or Eliminate waste water surcharges and pit cleaning




Midwestern works closely with commercial and industrial laundries to provide separator (lint screens) and tank systems that reduce the overall solids in liquid applications. Our stainless steel tanks can be manufactured to meet your specific volume requirements, in addition to supplying high quality Gyra-Vib® separators.

When implemented into a heat exchange system, laundries can reclaim valuable heat energy from wastewater. Laundries transfer heat from hot wastewater (approximately 130°F) through a heat exchanger and the incoming cold water temperature is raised to within five-degrees of the wastewater.

When pit wastewater with suspended solids is sent through a heat exchanger, the solids gradually reduce the heat exchanger's efficiency ultimately plugging its pipes. A ME or MR Series Gyra-Vib® separator can reduce solids to an acceptable level before the wastewater goes through the system – plugging is eliminated.

To save valuable floor space the separator can be mounted directly above the stainless steel tank. The screened, hot, wastewater is stored in the tank until it is pumped to the heat exchanger.



The pit's sloping bottom directs fibers and solids to the low corner from where it is then pumped to the separator. Water that goes to the screen passes through a separator feeder, reducing splashing and aeration. Screened wastewater is discharged into the stainless steel tank, then pumped to a heat exchanger, where incoming cold water is heated.





MIDWESTERN INDUSTRIES, INC.

TOLL FREE

877-4-SIZING
(877-474-9464)
WWW.MIDWESTERNIND.COM

MIDWESTERN'S WIRE MESH COMPARISON CHART

		• • • • • • • • • • • • • • • • • • • •	Tensil Bolting Cloth					oth		Mill	Grade		Market Grade			
Approx.	MM	US	OPG.	Tyler	Mesh	OPG.	Wire	% OA	Mach	OPG.	Wire	% OA	Mach	OPG.	Wire	% OA
Microns	1-11-1	Sieve	OPG.	Eqiv.	Mesii	OPG.	WITE	70 OA	Mesii	OFG.	wiie	70 OA	Mesii	OFG.	WIIE	70 OA
25000	25.0	1"	1.00													
19000	19.0	3/4"	.750													
16000 14288	16.0 14.3	5/8" 9/16"	.625 .562										_			
12500	12.5	1/2"	.500													
11200	11.2	7/16"	.438						2	.446	.054	79.6	2	.437	.063	76.4
9500	9.5	3/8"	.375													
8000	8.0	5/16"	.312													
6300	6.3	1/4"	.250						3	.292	.041	76.7	3	.279	.054	70.1
5600	5.6	3.5	.223	3.5					4	.215	.035	74.0	4	.2023	.0475	65.9
4750	4.75	4	.187	4					_	160	022	70.6	4	.187	.063	56.0
4000	4.0 3.35	5	.157	5					5 6	.168	.032	70.6 69.6	5 6	.159	.041	63.2 62.7
2800	2.80	6 7	.110	7					7	.115	.028	64.8	7	.108	.035	57.2
2360	2.36	8	.0937	8					8	.100	.025	64.0	8	.0964	.0286	60.2
2000	2.0	10	.0787	9					9	.088	.023	62.7	10	.0742	.0258	56.3
1854	1.85								10	.080	.020	64.0	11	.073	.018	64.5
1700	1.7	12	.0661	10	14	.062	.009	76.4	12	.065	.018	60.8	12	.0603	.023	51.8
1400	1.4	14	.0555	12	16	.0535	.009	73.3	14	.054	.017	57.2	14	.051	.0204	51.0
1180	1.18	16	.0469	14	18	.0466	.009	70.2	16	.0465	.016	55.4	16	.0445	.0181	50.7
1041	1.04	40	0004		20	.0410	.009	67.2	10	0406	015	F2 4		0006	0470	40.0
1000	1.0 .85	18 20	.0394	16 20	22 24	.0380	.0075	69.7 69.2	18 20	.0406	.015	53.4 51.8	18 20	.0386	.0173 .0162	48.3 46.2
850 787	.787	20	.0331	20	26	.0342	.0075	64.8	22	.0320	.0135	49.6	20	.034	.0102	40.2
710	.71	25	.0278	24	28	.0282	.0075	62.4	24	.0287	.0133	47.4	24	.0277	.014	44.2
681	.681		10270		30	.0268	.0065	64.8	26	.0275	.011	51.1		102//	.011	
630	.63				32	.0248	.0065	62.7	28	.0257	.010	51.8				
600	.60	30	.0234	28	34	.0229	.0065	60.7	30	.0238	.0095	51.0				
541	.541				36	.0213	.0065	58.7	32	.0223	.009	50.9				
500	.50	35	.0197	32	38	.0198	.0065	56.7	34	.0204	.009	48.1	30	.0203	.0128	37.1
470	.47				40	.0185	.0065	54.8	36	.0188	.009	45.8				
465	.465				42 44	.0183	.0055	59.1	38	.0178	.0085	45.8	25	0176	0110	27.0
437 425	.437 .425	40	.0165	35	46	.0172	.0055	57.4 55.8	40	.0165	.0085	43.6	35	.0176	.0118	37.9
389	.389	40	.0103	33	48	.0153	.0055	54.2	40	.0105	.0003	45.0	40	.0150	.0104	36.0
368	.368				50	.0145	.0055	52.6							.0201	50.0
355	.355	45	.0139	42	52	.0137	.0055	51.0	45	.0142	.008	40.8				
330	.33				54	.0130	.0055	49.4								
323	.323				58	.0127	.0045	54.6								
310	.31				60	.0122	.0045	53.3	50	.0125	.0075	39.1				
300	.30	50	.0117	48	62	.0116	.0045	51.7	55	.0112	.007	37.9		0110	0000	20.2
282 270	.282				64 70	.0111	.0045	50.7 54.9					50	.0110	.0090	30.3
260	.26				72	.0102	.0037	53.8								
250	.25	60	.0098	60	74	.0098	.0037	52.7	60	.0102	.0065	37.5				
241	.241				76	.0095	.0037	51.7								
231	.231				78	.0091	.0037	50.6					60	.0092	.0075	30.5
224	.224				80	.0088	.0037	49.6								
212	.212	70	.0083	65	84	.0084	.0035	49.8								
200	.20				88	.0079	.0035	47.9								
193	.193	90	0070	90	90	.0076	.0035	47.8					- 00	0070	OOFF	21.4
180 165	.18 .165	80	.0070	80	94 105	.0071	.0035	45.0 46.9					80	.0070	.0055	31.4
150	.15	100	.0059	100	120	.0058	.0025	47.3					100	.0055	.0045	30.3
125	.125	120	.0049	115	145	.0047	.0023	46.4					120	.0046	.0037	30.5
106	.106	140	.0041	150	165	.0042	.0019	47.1					150	.0041	.0026	37.9
90	.090	170	.0035	170	200	.0034	.0016	46.2					180	.0033	.0023	34.7
75	.075	200	.0029	200	230	.0029	.0014	46.0					200	.0029	.0021	33.6
63	.063	230	.0025	250									250	.0024	.0016	36.0
53	.053	270	.0021	270	300	.0021	.0012	40.5					270	.0021	.0016	32.2
45	.045	325	.0017	325									325	.0017	.0014	30.5
38 25	.038	400 500	.0015	400									400 500	.0015	.0010	36.0 25.0
20	.020	635	.0008										635	.0008	.0008	25.0
20	1020	000	.0000						•				000	.0000	.0000	20.0



