

PathWay® Model 4408 Single Channel Cat5e RJ45 A/B Switch, with Contact Closure Remote

INTRODUCTION:

The PathWay® Model 4408 Single Channel Cat5e RJ45 A/B Switch with Contact Closure Remote allows the user the capability of sharing a single port interface device connected to the "COMMON" port among two other devices connected to the "A" and "B" ports with remote access functionality. The Model 4408 dimensions are 5.25" W x 2" H x 7.25" D.

The switch may be controlled locally by manually operating the front panel pushbutton or remotely from the Terminal Strip Remote Control port located on the rear of the unit. The Terminal Strip Remote port provides contact closure control. The front panel LED display indicates the switch position and unit power status.

FEATURES:

- Allows quick connection to any one of two devices from one COMMON device.
- Switches all 8 pins of the RJ45 interface.
- Transparent to data speed and format.
- Certified for Cat 5e compliance.
- Local control via front-panel pushbutton.
- Remote control port allows off-site switch management.
- Front panel LED's display switch position and power status.
- Retains last switch position even in the event of power loss and continues to pass data.
- Attractive anodized black box packaging provides EMI/RFI shielding.
- Custom length Cat 5e cables available for your switch installation.



SPECIFICATIONS:

PORT CONNECTORS: (3) RJ45 female connectors labeled A, B, and COMMON.

FRONT PANEL CONTROLS: (1) Front panel pushbutton allows selection of switch position.

DISPLAY: (2) Front panel LED's display switch position and power status.

REMOTE CONTROL: (1) Terminal Strip on rear panel accepts Contact Closure signaling for remote control operation.

POWER: UL approved 120VAC, 60Hz wall mount power module supplies 12 VDC, 500 mA to the unit.

DIMENSIONS: Desktop, 5.25" W x 2.0" H x 7.25" D. (13.3 x 5.1 x 18.4 cm)

WEIGHT: Approximately 2.5 lbs. (1.1 Kg)

OPTION: WIDE RANGE POWER MODULE (Cat No 517277) CE and UL listed table mount power module, 100VAC/240VAC, 50Hz/60Hz in place of standard 115VAC or 120VAC power module. Ideal for international applications.

Model 4408 Application

