

PathWay® Model 7748 RS530 DB25 A/B Switch with Cutoff Position, 10/100Base-T Remote Port and GUI

INTRODUCTION

The PathWay® Model 7748 RS530 DB25 A/B Switch with Cutoff Position and 10/100BASE-T LAN Telnet Access and GUI, allows the user the capability of sharing a single port interface device connected to the "COMMON" port among two other devices connected to the "A" and "B" ports with remote. A front panel pushbutton allows local control of switch position. Remote Control access can be accomplished using an Ethernet 10/100BASE-T connection and either Telnet commands or graphical user interface.

FEATURES:

- The switch ports are transparent to all data.
- All pins of the DB25 interface are switched.
- When power is lost, unit reverts to a cutoff position that isolates all communication ports.
- When power is restored, the unit automatically switches to the default position set by the user.
- Control of the switch position from a 10/100-Base-T LAN Ethernet environment.
- Remote Control Telnet command interface or Graphical User Interface that allows the user to control switch position, lockout front panel operations and obtain switch status.
- Front panel LEDs display switch position and power status.

SOFTWARE FEATURES:

- Access User Interface via standard web browser.
- Easy to use, simple point and click operation.
- Remotely access to control or monitor the Model 7748 Switch System.
- Users can change the switch's IP address.
- LAN access gives users access across the LAN or over the Internet access to control if user network is configured accordingly.



SPECIFICATIONS:

PORT CONNECTORS:

- (2) DB25 male connectors labeled A and B.
- (1) DB25 female connector labeled COM.

FRONT PANEL CONTROL: (1) manual pushbutton allows local switching.

DISPLAY: (2) Front panel LED's display switch position and power status.

REMOTE CONTROL: (1) RJ45 female connector on rear panel accepts 10/100-Base-T LAN Access Ethernet interface port for Remote Control Operation.

POWER: UL approved 120VAC, 60 Hz wall mount power module supplies 12 VDC, 500mA to the unit

DIMENSIONS: Rackmount:
19.0" W x 1.75" H x 8.0" D.

WEIGHT: Approximately 4.5 lbs

OPTION: WIDE RANGE POWER MODULE

(Cat No 517277) CE and UL listed table mount power module, 100VAC/240VAC, 50Hz/60Hz in place of standard 115VAC or 120VAC power module. Ideal for international applications.

Model 7748 Application

