

Model 9258 Six-Channel RS530 DB25 A/B Switch

INTRODUCTION

The Model 9258 Six-Channel RS-530 DB25 A/B Switch, allows the user six independent channels of A/B switch function. The A/B function permits access by either of two devices connected to ports A and B, to a single COMMON port. The Model 9258 is a manual switch and requires no power. The Model 9258 is configured to mount in a standard 19 inch equipment rack within 1U of rack space. The dimensions of the unit are 19" W x 3.5" H x 8" D.

FEATURES

- Each channel allows quick connection to any one of two devices from one COMMON device.
- High quality sealed switch with self-wiping low impedance contacts.
- Eliminates the need to plug and unplug cables.
- No external power required.
- Transparent to data speed and format.
- Manual operation via front-panel rotary switches.
- Attractive anodized black box packaging provides EMI/RFI shielding.
- Custom length DB25 cables available for your switch installation.
- All DB25 pins of the DB25 interface are switched.
- Independently switch each of the six channels via knobs on front panel.
- Improves computer network efficiency by allowing sharing of peripherals.
- Lifetime guarantee against manufacturing defects.



SPECIFICATIONS:

PORT CONNECTORS: (18) DB25 female connectors labeled A, B, and COMMON. (Three for each of six channels)

FRONT PANEL CONTROLS: (6) Rotary Switches on front panel, one knob per channel, to switch each channel independently.

PINS SWITCHED: All 25 pins switched.

POWER: No power is required.

DIMENSIONS: Rackmount configuration 19.0" W x 3.5" H x 8.0" D. (48.3 x 8.9 x 20.3 cm)

WEIGHT: Approximately 8.0 lbs. (3.6 kg)

Model 9258 Application: Four independent A/B switch functions

